

TECHNICAL DESCRIPTION OF THE PRODUCT

Technical Data Sheet (TDS)



GLE M-14DCL40 (CD 40)

Motor oil for marine diesels.



Description

It is used for lubrication of medium-speed marine diesels with circulating or combined lubrication system when working on heavy fuel with a sulfur content of more than 2.5%.

It is made of high-quality base oils with the addition of additives.

Packing is available

Barrel 200l

Pouring

Advantages

- Good moisture resistance and low ability to emulsify with water;
- Easy separation of water during separation;
- Large stock of alkalinity, which provides excellent cleaning and neutralizing ability of the oil throughout the operation;
- Reliable protection against scale deposits;
- Good anti-wear and anti-corrosion properties, high thermal-oxidative stability;
- It is characterized by resistance to foaming.

Compliance

SAE 40 | API CD |

Typical characteristics

Kinematic viscosity at 100°C, mm ² /c	14.3
Viscosity index	94
Alkaline number, mg KOH/g	38
Flash point in open crucible, °C	238
Freezing point, °C	-11

Application temperature range



Produced in accordance with TU U 23.2-31852954-039: 2008.

This information is for reference only and is subject to change without notice.

This publication from 01.09.2014 replaces all previously published descriptions of this product.